

SPRO[®]

DHD80/ARW/60M-T-M

8 Megapixel HDCVI IR Turret Camera
With Microphone Built-in



8 MEGAPIXEL



2.7-13.5 MM



60m IR



MICROPHONE




IP67



Key Features:

- 8 megapixel
- 2.7-13.5mm motorised Lens
- Up to 60m IR distance (smart IR)
- Microphone built-in
- Audio over co-ax
- Audio on/off (controlled by DVR)
- IP67 waterproof
- DC12V



SPECIFICATIONS



| | |
|---------------------------------|---------------------------------|
| Model Number | DHD80/ARW/60M-T-M |
| Image Sensor | 1/2.7" CMOS |
| Effective Pixels | 3840 (H)×2160 (V), 4K |
| Electronic Shutter Speed | 1/3s-1/100000s |
| Min. Illumination | 0.03Lux/F1.7, 30IRE, 0Lux IR on |
| Max. IR LEDs Length | Up to 60m |
| IR On/Off Control | Auto/ Manual |
| IR LEDs | 2 |

(continued)

| Lens | |
|--------------------------------|--|
| Lens Type | Motorized |
| Mount Type | φ14 |
| Focal Length | 2.7mm–13.5mm |
| Max Aperture | F1.7 |
| Angle of View | H.: 105°–33°, V.: 56°–18°, Diagonal: 126°–38° |
| Iris type | Fixed Iris |
| Auto Focus | Yes |
| Close Focus | 0.8m (2.62ft) |
| DORI Distance | Detect: 90-264m Observe: 36-264m Recognize: 18-53m Identify: 9-26m |
| Pan/Tilt/Rotation | |
| Pan/Tilt/Rotation Range | Pan:0°~360° / Tilt: 0° ~ 78° / Rotation: 0° ~ 360° |
| Video | |
| Resolution | 4K (3840×2160); 5M (2592×1944); 4M (2560×1440); 960H (960× 576/960×480) |
| Video Frame Rate | CVI: 4K@15fps; 5M@20fps; 4M@25fps, CVBS: PAL/NTSC, |
| Day/Night | Auto switch by ICR |
| BLC Mode | BLC / HLC / WDR |
| WDR | 120dB/WDR |
| White Balance | Auto / Manual |
| Gain Control | Auto; manual |
| Noise Reduction | 2D&3D NR |
| Smart IR | Yes |
| Electronic Defog | Yes |
| Digital Zoom | 4X |
| Mirror | Off/On |
| Privacy Masking | Off/On (8 area, rectangle) |
| Port | |
| Video Output | Video output: HDCVI |
| Audio Input | One channel, built-in mic (-A) |

General

| | |
|-----------------------------|--|
| Power Supply | 12V DC \pm 30% |
| Power Consumption | Max 7.8W (12V DC, IR on) |
| Operating Conditions | -30°C ~ +60°C / Less than 95% RH |
| Storage Conditions | -30°C ~ +60°C / Less than 95% RH |
| Ingress Protection | IP67 |
| Casing | Metal throughout the whole casing |
| Dimensions | Φ 122.0mm \times 104.8mm (Φ 4.80" \times 4.13") |
| Net Weight | 0.58kg (1.28lb) |
| Gross Weight | 0.73kg (1.616lb) |



All specifications are subject to change without notice. Copyright © Luxrite Ltd. All rights reserved