

SPRO[®]**IP**

DHIPD40/28LRG-MS-V2

4MP IP Active Deterrence LITE Turret Camera



COLOUR NIGHT 2.0
SMART DUAL ILLUMINATION

**ACTIVE
DETERRENCE
LITE**

SPEAKER
Built-in

AI
ARTIFICIAL
INTELLIGENCE

TWOWAY AUDIO



AUDIO
OVER CAT5e CABLE

ONVIF

Key Features:

- H.265
- 4 Megapixel
- 2.8mm Fixed Lens
- Microphone built-in
- Speaker / Siren built-in
- Classification of Human & Vehicle
- Warm Light Range: Up to 30m
- IR range: Up to 30m
- Two-way-Audio
- Perimeter Protection
- SMD+
- 120dB WDR
- Metal Housing
- IP67 Waterproof
- DC12V/POE

SPECIFICATIONS

Model Number	DHIPD40/28LRG-MS-V2
Image Sensor	1/2.9" CMOS
Effective Pixels	2688 (H) × 1520 (V)
ROM	128 MB
RAM	128 MB
Scanning System	Progressive

(continued)

Electronic Shutter Speed	Auto/Manual 1/3 s–1/100000 s
Min. Illumination	0.004 lux@F1.0 (Colour, 30 IRE) 0.0004 lux@F1.0 (B/W, 30 IRE) 0 lux (Illuminator on)
S/N Ratio	> 56 dB
Illumination Distance	30 m (98.43 ft) (IR); 30 m (98.43 ft) (Warm light)
Illuminator On/Off Control	Auto/Manual
Illuminator Number	1 (IR LED); 1 (Warm light)
Pan/Tilt/Rotation Range	Horizontal: 0°–360°; vertical: 0°–78°; rotation: 0°–360°

Lens

Lens Type	Fixed focal
Mount Type	M12
Focal Length	2.8 mm
Max. Aperture	F1.0
Field of View	H: 101.6°; V: 54.8°; D: 122.1°
Iris Type	Fixed
Close Focus Distance	2.8 mm: 1.4 m (4.59 ft)
DORI Distance	Detect: 63.8 m Observe: 25.5 m Recognise: 12.8 m Identify: 6.4 m

Intelligence


IVS (Perimeter Protection)	Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
Smart Search	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos
SMD	SMD Plus

Video

Video Compression	H.265; H.264; H.264H; H.264B; MJPEG (only supported by the sub stream)
Smart Codec	Smart H.265+/ Smart H.264+
Video Frame Rate	Main stream: 2688 × 1520@(1–20 fps)/2560 × 1440@(1–25/30 fps); sub stream: 704 × 576@(1–25 fps)/704 × 480@(1–30 fps); *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Stream Capability	2 streams
Resolution	4M (2688 × 1520); 3.6M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Bit Rate Control	CBR/VBR
Video Bit Rate	H.264: 32 Kbps–6144 Kbps H.265: 12 Kbps–6144 Kbps
Day/Night	Auto(ICR) / Colour / B/W
BLC	Yes
HLC	Yes
WDR	120 dB
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom
Gain Control	Auto/Manual
Noise Reduction	3D NR
Motion Detection	OFF/ON (4 areas, rectangular)
Region of Interest(RoI)	Yes (4 areas)
Smart LED	Yes
Image Rotation	0°/ 90°/ 180°/ 270° (Support 90° / 270° with 2688×1520 resolution and lower.)
Mirror	Yes
Privacy Masking	4 areas
Audio	
Built-in MIC	Yes
Built-in Speaker	Yes
Audio Compression	G.711a; G.711Mu; PCM; G.726
Alarm	
Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; tripwire; intrusion; audio detection; voltage detection; SMD; security exception
Network	
Network	RJ-45 (10/100 Base-T)

SDK and API	Yes
Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP; NFS; P2P; auto registration
Interoperability	ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone;
User/Host	6 (Total bandwidth: 36 M)
Storage	FTP; SFTP; Micro SD Card (support max. 256 G);
Browser	IE, Chrome, Firefox
Management Software	DMSS
Mobile Phone	iOS & Android
Cyber Security	Configuration encryption;Trusted execution;Digest;Security logs; WSSE;Account lockout;syslog;Video encryption;802.1x;IP/MAC filtering;HTTPS;Trusted upgrade;Trusted boot;Generation and importing of X.509 certification
Certification	
Certifications	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU
Power	
Power Supply	12V DC/PoE
Power Consumption	Basic: 2 W (12 VDC), 2.6 W (PoE) Max. (H.265 + intelligence on + WDR + IR intensity + warm light deterrence + speaker): 8.6 W (12 VDC), 10.1 W (PoE)
General	
Operating Temperature	−40 °C to +60 °C (−40 °F to +140 °F)
Operating Humidity	≤95%
Storage Temperature	−40 °C to +60 °C (−40 °F to +140 °F)
Storage Humidity	≤95%
Protection	IP67
Casing Material	Inner core: Metal - Cover: Plastic
Product Dimensions	89.2 mm × Φ105 mm
Net Weight	0.39 kg (0.86 lb)
Gross Weight	0.57 kg (1.26 lb)



All specifications are subject to change without notice. Copyright © Luxrite Ltd. All rights reserved