

SPRO^{IP}

COLOURNIGHT 2.0

SMART DUAL ILLUMINATION



DHIPD60/28LRG-M

6MP Smart Dual Illumination Fixed-focal Eyeball Network Camera



Key Features:

- H.265
- 6 Megapixel
- 2.8mm Fixed Lens
- Microphone built-in
- Classification of Human & Vehicle
- Warm Light Range: Up to 30m
- IR range: Up to 30m
- Perimeter Protection
- SMD+
- 120dB WDR
- Metal Housing
- IP67 Waterproof
- DC12V/POE



SPECIFICATIONS

Model Number	DHIPD60/28LRG-M
Image Sensor	1/2.7" CMOS
Max. Resolution	3288 (H) × 1850 (V)
ROM	128 MB
RAM	256 MB
Scanning System	Progressive

(continued)

Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Min. Illumination	0.007 lux@F1.6 (Colour, 30 IRE) 0.0007 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on)
S/N Ratio	>56 dB
Illumination Distance	30 m (98.43 ft) (IR); 30 m (98.43 ft) (Warm light)
Illuminator On/Off Control	Auto/Manual
Illuminator Number	1 (IR LED); 1 (Warm light)
Pan/Tilt/Rotation Range	Pan: 0°–360°; Tilt: 0°–78°; Rotation: 0°–360°
Lens	
Lens Type	Fixed-focal
Mount Type	M12
Focal Length	2.8 mm
Max. Aperture	F1.6
Field of View	H: 112°; V: 61°; D: 132°
Iris Type	Fixed
Close Focus Distance	1.0 m (3.28 ft)
DORI Distance	Detect: 61.2 m Observe: 24.5 m Recognise: 12.2 m Identify: 6.1 m
Intelligence	
IVS (Perimeter Protection)	Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
Smart Search	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos
SMD	SMD Plus
Video	
Video Compression	H.265; H.264; H.264H; H.264B; MJPEG (only supported by the sub stream)
Smart Codec	Smart H.265+/ Smart H.264+
Video Frame Rate	Main stream: 3288 × 1850@(1–20 fps)/2688 × 1520@(1–25 fps) sub stream: 704 × 576@(1–25 fps)/704 × 480@(1–25 fps) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Stream Capability	2 streams
Resolution	6M (3288 × 1850/3200 × 1800); 5M (2880 × 1620); 4M (2688 × 1520); 3M (2048 × 1536/2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Bit Rate Control	VBR;CBR
Video Bit Rate	H.264: 32 kbps–8192 kbps; H.265: 12 kbps–8192 kbps
Day/Night	Auto(ICR) / Colour / B/W
BLC	Yes
HLC	Yes
WDR	120 dB
White Balance	Auto / natural / street lamp / outdoor / manual / regional custom
Gain Control	Auto / Manual
Noise Reduction	3D NR
Motion Detection	OFF/ON (4 areas, rectangular)
Region of Interest(RoI)	Yes (4 areas)
Smart Illumination	Yes
Smart Dual Light	Yes
Image Rotation	0°/ 90°/ 180°/ 270° (Support 90° / 270° with 2688×1520 resolution and lower.)
Mirror	Yes
Privacy Masking	4 areas
Audio	
Built-in MIC	Yes, built-in Mic
Audio Compression	G.711a; G.711Mu; PCM; G.726
Alarm	
Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; tripwire; intrusion; audio detection; voltage detection; SMD; security exception


Network	
Network Port	RJ-45 (10/100 Base-T)
SDK and API	Yes
Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; P2P; Bonjour; Auto Registration
Interoperability	ONVIF (Profile S & Profile G & Profile T); CGI
User/Host	20 (Total bandwidth: 48M)
Storage	FTP; SFTP; Micro SD card (Support max. 256GB); NAS
Browser	IE; Chrome; Firefox
Management Software	DMSS, Smart PSS Lite
Mobile Client	iOS; Android
Cyber Security	Video encryption;Firmware encryption;Configuration encryption; Digest;WSSE;Account lockout;Security logs;IP/MAC filtering; Generation and importing of X.509 certification;syslog;HTTPS; 802.1x;Trusted boot;Trusted execution;Trusted upgrade
Certification	
Certifications	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU
Power	
Power Supply	12VDC; PoE
Power Consumption	Basic: 2.5W (12 VDC); 3.4W (PoE); Max.: 4.6W (12 VDC); 5.7W (PoE) (H.265 + intelligence on + WDR + illuminator intensity)
Environment	
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	≤95% (RH), non-condensing
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Storage Humidity	≤95% (RH), non-condensing
Protection	IP67

Structure

Casing Material	Metal
Product Dimensions	100.9 mm × Φ109.9 mm (3.90" × Φ4.33")
Net Weight	0.38Kg (0.84lb)
Gross Weight	0.52Kg (1.15lb)

Dimensions (mm[inch])

mm [inch]



All specifications are subject to change without notice. Copyright © Luxrite Ltd. All rights reserved